

MONO CRYSTALLINE HALF-CUT MODULE

370 / 375 / 380 / 385 / 390 Watts


Black Panther



Overview

Ground breaking technology: higher power output, improved system performance - the ideal solution for end users who want a fast turnaround on their investments. A fully certified premium quality and high efficiency module made with A Grade materials.

Key Benefits



Certified by Independent Engineering Bodies



Product Liability Insurance



Ultra High Power Output




15 Years Limited Product Warranty



Low Resistive Losses



Low LCOE



Guaranteed mechanical resistance to severe weather conditions



Positive Tolerance




100 % electro-luminescence tested

Tests, Certifications and Warranties

Standard Tests	IEC 61215, IEC 61730
Factory Quality Tests	ISO 9001: 2015, ISO 14001: 2015
Certifications	Conformity to CE, PV CYCLE Fire safety Class C according to UL790
Insurance	Product liability insurance provided by Allianz
Wind and Snow Loads Testing	Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal)
Power Tolerance	Guaranteed +0%/+5% (STC condition)
Warranties	<ul style="list-style-type: none"> 15-year limited product warranty 15-year manufacturer warranty on 90.44% of the nominal performance 25-year transferable linear power output warranty

Linear Performance Warranty



First Year Output $\geq 98\%$ 2-25 Year Decline $\leq 0.54\%$ 25 Year Output $\geq 85.04\%$

MONO CRYSTALLINE HALF CUT MODULE

RCM-xxx-6MM (xxx=370-390)


Electrical Characteristics

POWER CLASS ⁽¹⁾			370		375		380		385		390	
Testing Condition			STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power	Pmax	[Wp]	370	273.97	375	277.67	380	281.37	385	285.08	390	288.78
Maximum Power Voltage	Vmp	[V]	36.05	33.31	36.26	33.51	36.47	33.70	36.68	33.90	36.89	34.09
Maximum Power Current	Imp	[A]	10.27	8.21	10.35	8.28	10.42	8.33	10.50	8.40	10.58	8.46
Open Circuit Voltage	Voc	[V]	43.64	43.34	43.89	43.59	44.15	43.85	44.40	44.10	44.66	44.35
Short Circuit Current	Isc	[A]	10.85	8.71	10.94	8.78	11.01	8.84	11.10	8.91	11.18	8.97
Module Efficiency	Eff	[%]	18.52		18.77		19.02		19.27		19.52	
Maximum Series Fuse	IR	[A]	20									
Maximum System Voltage	Vsys	[V]	1500 DC									
(1) Measurement Tolerances: Pmax (± 3%), Isc & Voc (± 5%) - Power Classification 0/+5W												
(2) STC (Standard Testing Condition): Irradiance 1000W/m², Cell Temperature 25°C, AM 1.5												
(3) NMOT (Nominal Operating Module Temperature): Irradiance 800W/m², NMOT, Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s												

Mechanical Data

Dimensions	1925 mm x 1038 mm x 35 mm
Weight	21.8 Kg
Cell Type	Mono Perc - 166mm x 83mm (2 x 66 Pcs) -M6
Front Glass	3.2mm low-iron tempered suede glass + ARC
Rear Side	Anti-aging film
Frame	Anodized Aluminium alloy
Junction Box	IP68 rated - 3 Bypass diodes
Connector	EV02 Compatible
Output cable	4mm² - Length = 1200mm or can be customized

Dimensions




RECOM assumes no liability or responsibility for any typographical error, layout error, misinformation, any other error, omission, contained herein.

recom-solar.com

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, RECOM Solar reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Please read the safety and installation instructions before using the modules.

I-V Curve

The module relative power loss at low light irradiance of 200W/m² is less than 3%.



Temperature Characteristics

Pmax Temperature Coefficient	-0.365% / °C
Voc Temperature Coefficient	-0.285% / °C
Isc Temperature Coefficient	+0.055% / °C
Operating Temperature	-40~+85 °C
Nominal Operating Module Temperature (NMOT)	42 ± 2°C

Packing Configuration

Container	40'HC
Pieces per Pallet	30
Pallets per Container	24
Pieces per Container	(30+30+4)x12=768 pcs