

# MPPT SOLAR CHARGE CONTROLLER

LCD / LED  
5 A ~ 60 A



## FEATURES

- Unattended:** PV auto-start and auto-charging, no need of manual operation
- High efficient MPPT:** Multiple Power Point Trackers (MPPTs) enable the output power of solar panel array to be at maximum state, improving the energy conversion 20% ~ 30%
- High reliability:** Adopt advanced microprocessor to achieve "MPPT + SOC" dual intelligent optimized charging control to ensure the product to be stable and reliable
- Intelligent charging management:** Adopt charging mode combined constant current and constant voltage to ensure effective battery charging and battery life
- Battery protections:** Automatically test the battery running condition. The system will automatically shut down in the event of overdischarge to avoid consuming the battery energy
- High efficiency:** Adopt low power consumption MOSFET and PWM soft switch and synchronous rectifier technology, effectively improving the system operating efficiency
- Intelligent:** Auto-start by illumination recognition (optional) – the system can configure auto start the load in the event of insufficient sunshine, such as fog, rain, night etc
- Protections:** Overcharge / overdischarge, short circuit, overload, reverse connection, TVS lightning protection etc
- Strong adaptability (optional):** Charging voltage is settable to adapt to lithium battery and lead-acid battery
- Communications (optional):** RS232 and dry contacts port for communication and real-time monitoring
- Temperature compensation (optional):** The test interface of ambient temperature of the external battery group is available.

The battery charging voltage is adjustable in real time according to the ambient temperature of the battery

# POWER MAXMA

MPPT Solar Charge Controller

## SPECIFICATIONS

MODEL	F12-05/10/M	F12-20	F24-05/10/M	F24-20	F1224-10/20/30 /40/50/60M F2448-10/20/30 /40/50/60M		
Display	LED			LCD + LED			
Rated voltage	12 V			24 V			
Max. charging current	5 / 10 A	20 A	5 / 10 A	20 A	10/20/30/40/50/60A		
Max. load current	5 / 10 A	20 A	5 / 10 A	20 A	10/20/30/40/50/60A		
Max. PV power	12 V - 05 A 60 W 12 V - 10 A 120 W	240 W	24 V - 05 A 120 W 24 V - 10 A 240 W	480 W	12V-120/240/360/480/600/720W 24V-240/480/720/960/1200/1440W 48V-480/960/1440/1920/2400/2880W		
Battery capacity (lead-acid)	17 Ah ~ 400 Ah			38 Ah ~ 800 Ah			
Max. efficiency	≥ 98%						
Max. PV input voltage	F1224 (12 V: 0 ~ 30 V; 24 V: 0 ~ 60 V); F2448 (24 V: 0 ~ 48 V; 48 V: 0 ~ 96 V)						
Optimum operating voltage of PV (Vmp)	12 V: 15 ~ 22 V; 24 V: 29 ~ 38 V; 48 V: 58 ~ 72 V						
Equalizing charge voltage	12 V: 14.6 V ± 1%; 24 V: 29.2 V ± 1%; 48 V: 58.4 V ± 1%						
Floating charge voltage	12 V: 14.4 V ± 1%; 24 V: 28.8 V ± 1%; 48 V: 57.6 V ± 1%						
Overcharge protections	12 V: 14.7 V ± 1%; 24 V: 29.4 V ± 1%; 48 V: 58.8 V ± 1%						
Charging fold-back voltage	12 V: 13.2 V ± 1%; 24 V: 26.4 V ± 1%; 48 V: 52.8 V ± 1%						
Undervoltage alarm	12 V: 11.2 V ± 1%; 24 V: 22.4 V ± 1%; 48 V: 44.8 V ± 1%						
Overdischarge protections	12 V: 10.8 V ± 0.3 V; 24 V: 21.6 V ± 0.3 V; 48 V: 43.2 V ± 0.4 V						
Overdischarge restoring start voltage	12 V: 13.2 V ± 0.3 V; 24 V: 26.4 V ± 0.3 V; 48 V: 52.8 V ± 0.4 V						
Overload / short circuit protections	110% for 255 s; 125% for 60 s; 150% for 10 s / Auto shutdown if short circuit						
PV reverse polarity protection	Available						
Communications (optional)	RS232 / dry contacts						
Operating temperature	-20°C ~ +45°C						
Storage temperature	-25°C ~ +85°C						
Max. altitude	1000 m at rated power (derating 1% for each additional 100 m); Max. 4000 m						
Relative humidity	0 ~ 95% (non-condensing)						
Storage humidity	≤ 85%						
Installation	Vertical wall mounting						
Dimensions (W × D × H) (mm)	136 × 100 × 35			164 × 168 × 55 (F1224-10/20/30M&F2448-10/20M) 164 × 168 × 100 (F1224-40/50/60M&F2448-30/40/50/60M)			
Packaged dimensions (W × D × H) (mm)	145 × 110 × 45			215 × 208 × 145			
Net weight (kg)	0.23			0.85 (F1224-10/20/30M&F2448-10/20M) 2.05 (F1224-40/50/60M&F2448-30/40/50/60M)			
Gross weight (kg)	0.28			1.05 (F1224-10/20/30M&F2448-10/20M) 2.25 (F1224-40/50/60M&F2448-30/40/50/60M)			

● All specifications subject to change without notice.