

Cell Specification (Prismatic)	Nominal Voltage (V)	Typical Capacity (Ah)	Charge Voltage (V)	Thickness (mm)	Width (mm)	Total Height (mm)	Application
PPF1865122	3.2	10	3.65	18.0	65.0	135.0	Energy storage
PPF2770132	3.2	20	3.65	27.0	70.0	145.0	Energy storage
PPF2770165	3.2	25	3.65	27.0	70.0	180.0	Energy storage
PPF32173115	3.2	50	3.65	32.0	173.0	130.0	Energy storage

Cell Specification (Cylindrical)	Nominal Voltage (V)	Typical Capacity (mAh)	Charge Voltage (V)	Diameter (mm)	Height (mm)	Max Continuous Discharge Current (A)	Application
CFP26650	3.2	3300	3.65	26.8	65.0	9.0	Energy storage
CFP26650	3.2	3500	3.65	26.8	65.0	9.0	Energy storage
CFP32650	3.2	5000	3.65	32.7	65.0	10.0	Energy storage

Battery Module Specification	Nominal Voltage (V)	Typical Capacity (AH)	Length (mm)	Width (mm)	Height (mm)	Approx Weight (KG)	Max Continuous Discharge Current (A)
12DF12	12.8	12.0	151.0	99.0	94.0	1.8	10
12DF20	12.8	20.0	181.0	77.0	171.0	2.7	20
12DF33	12.8	33.0	195.0	130.0	178.0	4.3	50
12DF40	12.8	40.0	197.0	165.0	175.0	5.6	50
12DF50	12.8	50.0	228.0	138.0	212.0	7.9	50
12DF75	12.8	75.0	259.0	169.0	211.0	10.7	50
12DF100	12.8	100.0	318.0	165.0	215.0	13.3	100
12DF125	12.8	125.0	318.0	165.0	215.0	15.9	100
12DF150	12.8	150.0	405.0	173.0	232.0	18.5	100
12DF200	12.8	200.0	522.0	240.0	244.0	26.7	100
24DF50	25.6	50.0	318.0	165.0	215.0	13.3	50
48DF10	48.0	10.0	480.0	260.0	44.0	7.5	5
48DF20	48.0	20.0	480.0	260.0	88.5	14.0	10
48DF20C	48.0	20.0	318.0	165.0	215.0	13.3	10
48DF50	48.0	50.0	480.0	260.0	134.0	35.0	20
48DF75	48.0	75.0	480.0	260.0	223.0	50.0	30

Aside from those products, DNP can provide customized packs according to the customer's needs and specifications.