

## Technical Specifications



	OFC 320
Power (Pm) in Watts (nominal)	320 (0~+3%)
Open Circuit Voltage (Voc) in Volts	45.5
Short Circuit Current (Isc) in Amps	9.25
Voltage at Maximum Power (Vmp) in Volts	37.0
Current at Maximum Power (Imp) in Amps	8.65
Maximum System Voltage	1000V
Solar Cells per Module (Units)	72
Length x Width x Thickness (L x W x T) mm	1960X990X35
Weight – Kg	23
Mounting Holes Pitch (Y) – mm	1200
Mounting Holes Pitch (X) – mm	958
Area – Sq. M	1.94
Junction Box	Ip67/4T with play & plug connector

\*All electrical parameters specified at STC: 25°C cell temperature; 1000W/M<sup>2</sup> irradiance; AM 1.5


### Construction Features

Type of cell	156 X 156mm Multi/Mono Crystalline Si
Glass	Tempered & Low Iron
Encapsulate	Ethylene Vinyl Acetate
Frame	Anodized Aluminum
Junction Box	Weather Proof Nylon 6


### Warranty

10 years Product Warranty
10 years – 90% of Power
25 Years – 80% of power

### I-V Curve at STC



### Mounting Details



### Temperature Coefficient

Voltage	-0.30% / °C
Current	0.07% / °C
Power	-0.38% / °C
NOCT	47±2 °C

\*Due to constant product modifications, **OFCA SOLAR** reserves the right to amend the above specifications without prior notice

**OFCA POWER TECHNOLOGY PVT. LTD.**

Plot No 124, Sector 4, IMT Manesar, GURGAON, HARYANA-122050

Ph: 0124-6520001 & 2290187, Email: info@ofcasolar.com

[www.ofcasolar.com](http://www.ofcasolar.com)