


EN156P-60-265/270/275/280W







Polycrystalline Solar Module 60-Cell Series

ABOUT ECONESS ENERGY

Established in 2009 by Jiangsu Huadong Group (founded in 1997), Econess Energy is a world's leading solution provider for solar energy. With annual production capacity of 800MW cells and 1.2GW modules. Econess Energy now distributes its PV products to over 36 countries with cumulative module shipment of 4GW. As a strong, bankable partner, we are committed to building strategic, mutually beneficial collaboration with installers and developers.



KEY FEATURES

-  **Maximize limited space**
Maximum power output 280W
-  **IP67 junction box**
The highest waterproof level
-  **Excellent Anti-PID performance**
2 times of industry standard
Anti-PID test by TUV
-  **Lower temperature coefficients**
Enhance power generation
-  **Highly reliable due to stringent quality control**
In-house testing goes well beyond certification requirements
-  **Certified to withstand the most challenging environmental conditions**
2400 Pa wind load · 5400 Pa snow load · 25mm hail stones at 82 km/h

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 1703
- ISO 9001 : 2015 Quality Management System
- ISO 14001 : 2015 Environment Mangement System
- OHSAS 18001 : 2007 Occupational Health and Safety Management System




QUALITY WARRANTY

ECONESS Energy guarantees that defects will not appear in materials and workmanship defined by IEC61215, IEC61730 or UL1703 under normal installation, use and maintenance as specified in Econess Energy's installation manual for 10 years from the warranty starting date.

PERFORMANCE WARRANTY

Polycrystalline Solar Module



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 - +3%)

Maximum Power(Pmax/W)	265	270	275	280
Operating Voltage (Vmpp/V)	31.04	31.35	31.71	32.05
Operating Current(Imp/A)	8.55	8.62	8.68	8.75
Open-Circuit Voltage (Voc/V)	38.22	38.51	38.69	39.02
Short-Circuit Current(Isc/A)	9.04	9.09	9.16	9.24
Module Efficiency η_m (%)	16.19	16.50	16.80	17.11

Performance at NMOT

Maximum Power(Pmax/W)	196	199	203	207
Operating Voltage(Vmpp/V)	28.66	28.83	29.12	29.37
Operating Current(Imp/A)	6.84	6.91	6.98	7.05
Open-Circuit Voltage(Voc/V)	35.18	35.47	35.63	35.93
Short-Circuit Current(Isc/A)	7.33	7.37	7.43	7.50

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

MECHANICAL SPECIFICATION

Cell Type	Poly
Cell Dimensions	6 inch
Cell Arrangement	60 (6 x 10)
Weight	18 kg (39.68 lb)
Module Dimensions	1650 x 992 x 35 mm (64.96 x 39.06 x 1.38 inch)
Cable Length	900 mm (47.24 inch)
Cable Cross Section Size	4 mm ² (0.006 sq.in)
Front Glass	3.2mm High Transmission, Tempered Glass
No.of Bypass Diodes	3/6
Packing Configuration (1)	31pcs/Pallet, 868pcs/40hq
Packing Configuration (2)	31pcs+4pcs/Pallet, 924pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP67


OPERATING CONDITIONS

Maximum System Voltage	1000V (IEC) DC / 1500V (IEC) DC
Operating Temp	-40°C ~ +85°C
Maximum Series Fuse	15A / 20A
Static Loading	5400 Pa
Conductivity at Ground	≤ 0.1Ω
Safety Class	II
Resistance	≥ 100MΩ
Connector	MC4 Compatible


TEMPERATURE COEFFICIENT

Temperature Coefficient(Pmax)	-0.40%/°C
Temperature Coefficient(Voc)	-0.31%/°C
Temperature Coefficient(Isc)	+0.06%/°C
NMOT	45 ± 2°C

I-V CURVE



TECHNICAL DRAWINGS (mm)



Econess Energy Co., Ltd.

58 Haida Road, Huashi, Jiangyin, Jiangsu, P.R. China 214421 +86-510-86076868 sales@eco-pv.com www.eco-pv.com

* This is preliminary datasheet and for reference only. The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Econess Energy reserves the right to make necessary adjustment to the information described herein at any time without further notice.