

**SKT575~600M10**

**575~600 Watt**

182mm 156Cells PV Solar Module



MBB PERC  
Half Cut Cell



Excellent Low-light  
Performance



100% Inspection  
Guarantee Reliability



Anti PID



5400Pa  
Strengthened  
Mechanical Load




High Density  
Packaging




# SKT575~600M10

182mm 156Cells Solar PV Module



All Dimensions in mm  
The above drawing is a graphical representation of the product.  
For engineering quality drawings please contact SUNKET.



## Electrical Characteristics (STC/NOCT)

Module Type	SKT575M10		SKT580M10		SKT585M10		SKT590M10		SKT595M10		SKT600M10	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power- Pmax(W)	575	428	580	432	585	435	590	439	595	443	600	447
Open Circuit Voltage - Voc(V)	53.43	50.43	53.54	50.54	53.65	50.64	53.76	50.75	53.87	50.86	53.98	50.97
Short- Circuit Current - Isc(A)	13.69	11.06	13.77	11.12	13.85	11.19	13.97	11.27	14.05	11.35	14.13	11.43
Voltage at Pmax -Vmp(V)	44.22	41.14	44.34	41.29	44.41	41.39	44.49	41.46	44.57	41.67	44.65	41.88
Current at Pmax - Imp(A)	13.01	10.41	13.09	10.47	13.18	10.51	13.27	10.59	13.36	10.63	13.45	10.67
Module Efficiency -ηm(%)	20.58	/	20.76	/	20.94	/	21.12	/	21.29	/	21.47	/
Power Tolerance(W)	(0, +4.99W)											
Maximum System Voltage(V)	1500Vdc (IEC / UL)											
Maximum Series Fuse Rating (A)	25A											

STC : Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25 C, Air Mass 1.5

NOCT : Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20 C, Air Mass 1.5, Wind Speed 1m/s

## Mechanical Specifications

External Dimensions	2464x1134x35mm
Weight	32kg
Solar Cells	Mono crystalline 182mm (2x78pcs)
Front Glass	AR Coated 3.2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm <sup>2</sup> , 50cm (+), 50cm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

## Packing Configuration

	2464x1134x35mm	
Container	20'GP	40'HQ
Pieces per Pallet	31	31
Pallets per Container	4	16
Pieces per Container	124	496

## Temperature Characteristics

Pmax Temperature Coefficient	-0.350%/ C
Voc Temperature Coefficient	-0.275%/ C
Isc Temperature Coefficient	+0.045%/ C
Operating Temperature	-40 ~ +85 C
Nominal Operating Cell Temperature(NOCT)	45±2 C

## Current-Voltage & Power-Voltage Curves (SKT600M10)

