

# Module Mounting System : Flat Roof Mounting System

## Adjustable Tripod Mounting



## Product Features

### 1. Simple Design

These products are factory assembled, well packaged, which highly reduce on site installation time by 40% compared to traditional type. Team of 4 professional labours can install 200KW in 1 day.

### 2. Universal

Use of universal mid and end clamps enables panel installation of thickness 35mm to 50mm. The tilt angle can be adjusted from 10 deg - 25deg. This product can adopt concrete block or ground screw piles as foundation.

This product can adopt concrete block or ground screw piles as foundation.

### 3. Safety and Reliability

The design has followed japan JIS standard and have obtained TUV and MCS certification.

### 4. 20 Years Warranty

Aluminum structure are treated with anodized layer of thickness 15, can stand up to the extreme weather conditions.

The main support components have also been tested to guarantee its structure and load-bearing capacity.

Pre assembled Tripod (folded)



Rail



Mid/End Clamps

## Technical Parameters

Install Site	Low profit roof or open field
Tilt Angle	10 deg - 25 deg
Max Wind Load	upto 60m/s
Snow Load	up to 1.4KN/m <sup>2</sup>
Warranty	20 Years
Certification	AS/NZS 1170, MCS, SGS
Material	Anodized Aluminum AL6005-T5
Fasteners	SUS304 A2-70
Yield Strength	260N/mm <sup>2</sup>

