

GTS-L Range

Special PP plastic with steel casing outside and extra thick design for battery plate, GTS-L range maximizes an outstanding performance to 20 years service life and deep cycle capacity, offering an ideal solution for large capacity valve regulated lead-acid battery's requirements with a compact, quick and simple installation process.

Applications

- Telecommunications-Central Office
- Telecommunication-Outside Plant
- Telecommunication-Wireless
- Photovoltaic Solar System
- UPS & BESS
- Electric Utility
- Emergency Power System



Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions								Weight Approx(kg)	
					L		W		H		Total Height			
		C10	C3	C1	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(Kg)	(lb)
GTS6-150LS	6	152	116	84	221	8.70	166	6.54	330	12.99	370	14.57	32.00	70.4
GTS6-200LS	6	210	150	112	275	10.83	165	6.50	330	12.99	370	14.57	41.30	90.9
GTS12-200L	12	200	150	113	665	26.18	330	12.99	218	8.58	218	8.58	92.00	202.4
GTS12-300L	12	300	225	139	893	35.16	330	12.99	218	8.58	218	8.58	131.00	288.2
GTS12-400L	12	400	300	226	779	30.67	516	20.31	218	8.58	218	8.58	170.00	374.0
GTS12-500L	12	500	375	282	957	37.68	516	20.31	218	8.58	218	8.58	209.00	459.8
GTS12-600L	12	580	450	336	1071	42.17	516	20.31	218	8.58	218	8.58	241.00	530.2
GTS6-800L	6	830	600	448	801	31.54	516	20.31	218	8.58	218	8.58	167.00	367.4
GTS6-1000L	6	1000	750	564	915	36.02	516	20.31	218	8.58	218	8.58	202.00	444.4
GTS6-1100L	6	1100	825	616	972	38.27	516	20.31	218	8.58	218	8.58	218.00	479.6
GTS6-1200L	6	1200	900	677	972	38.27	516	20.31	218	8.58	218	8.58	230.00	506.0
GTS4-1500L	4	1500	1125	856	793	31.22	465	18.31	277	10.91	277	10.91	205.00	451.0
GTS6-1500L	6	1500	1125	856	1147	45.16	465	18.31	277	10.91	277	10.91	303.00	666.6
GTS4-1600L	4	1600	1200	896	793	31.22	465	18.31	277	10.91	277	10.91	217.00	477.4
GTS6-1600L	6	1600	1200	896	1147	45.16	465	18.31	277	10.91	277	10.91	321.00	706.2
GTS4-1800L	4	1800	1350	1008	793	31.22	562	22.13	277	10.91	277	10.91	248.00	545.6
GTS6-1800L	6	1800	1350	1008	1147	45.16	562	22.13	277	10.91	277	10.91	371.00	816.2
GTS4-2000L	4	2000	1500	1128	793	31.22	562	22.13	277	10.91	277	10.91	382.00	840.4
GTS6-2000L	6	2000	1500	1128	1147	45.16	562	22.13	277	10.91	277	10.91	395.00	869.0

GT-G Range

GT-G range applies the advanced GEL design and the purity fumed silica to form sulfuric acid thixotropic Gel, and fills the batteries with vacuum to ensure complete penetration of electrolyte through separators and plates pastes.

This range battery has excellent cycling capability and superior float life to meet the requirement of frequent cyclic and high temperature application such as Cable TV, Telecommunication, boardband, PVs etc.

Applications

- Broadband
- Electric Powered Vehicle
- UPS
- Photovoltaic & Solar System
- Telecommunication



Specifications

Model	Nominal Voltage (V)	Nominal Capacity (20hr)(Ah)	Dimensions						H Over Terminal		Weight Approx(kg)	
			L		W		H		(mm)	(in)	(Kg)	(lb)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
GT12-33G	12	33	195	7.68	130	5.12	159	6.26	180	7.09	12.50	27.5
GT12-55G	12	55	230	9.06	138	5.43	206	8.11	210	8.27	17.50	38.5
GT12-75G	12	75	258	10.16	168	6.61	208	8.19	212	8.35	23.00	50.6
GT12-90G	12	90	305	12.01	168	6.61	208	8.19	212	8.35	28.90	63.6
G12-100G	12	100	330	12.99	172	6.77	215	8.46	221	8.70	31.50	69.3
GT12-100G-2	12	100	406	15.98	167	6.57	216	8.50	218	8.58	36.00	79.2
GT12-134G	12	134	341	13.43	172	6.77	282	11.10	288	11.34	42.00	92.4
GT12-200MG	12	200	498	19.61	259	10.20	218	8.58	238	9.37	72.00	158.4
GT12-200G	12	200	522	20.55	243	9.57	220	8.66	220	8.66	66.00	145.2