

# SINGLE PHASE & DUAL MPPT

## PV 4/5/6KTL-D1/G2

Application: Family Use



### SUPERIOR EFFICIENCY

- Maximum efficiency 98.2%
- String Current 13A, compatible with high Power modules
- 150% PV configuration, 110% output overload



### HIGH RELIABILITY

- IP65 waterproof and dustproof, C5 anti-corrosion
- Compatible with wide power grid voltage and high harmonic power grid environment
- DC /AC SPD optional, AFCI detection optional



### INTELLIGENT MAINTENANCE

- Remote configuration and upgrade
- Supports export power control

Model	PV 4KTL-D1/G2	PV 5KTL-D1/G2	PV 6KTL-D1/G2
<b>Efficiency</b>			
Max. Efficiency	98.0%	98.2%	98.2%
European Efficiency	97.0%	97.3%	97.4%
<b>Input(PV)</b>			
Max. Input Voltage	550V		
Max. PV configuration (STC)	150%		
Rated Input Voltage	360V		
Max. Input Current	26A (2*13A)		
Max.Short Circuit Current	30A (2*15A)		
Start Input Voltage	90V		
MPPT Operating Voltage Range	70V-540V		
Max. Number of PV Strings	2(1/1)		
No. of MPPTs	2		
<b>Output(Grid)</b>			
Rated AC Active Power	4,000W	5,000W	6,000W
Max. AC Apparent Power	4,400VA	5,500VA	6,000VA
Max. AC Active Power (PF=1)	4,400W	5,500W	6,000W
Max. AC Output Current	20A	25A	27.3A
Rated AC Voltage	220V/230V, L+N+PE		
AC Voltage Range①	160V-300V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range②	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5In		
Power Factor	>0.99 Rated power (Adjustable 0.8 Leading-0.8 Lagging)		
<b>Protection</b>			
DC switch	Support		
Anti-islanding protection	Support		
AC overcurrent protection	Support		
AC short circuit protection	Support		
DC reverse connection	Support		
Surge Arrester	DC Type III (Optional) / AC Type III		
Insulation detection	Support		
Leakage current protection	Support		
<b>General</b>			
Topology	Transformerless		
IP Rating	IP65		
Night Self Consumption	<1W		
Cooling	Natural cooling		
Operating Temperature Range	-25°C-60°C		
Relative Humidity Range	0-100%		
Max. Operating Altitude	4000m		
Noise (typical)	30dB		
Dimensions (W*H*D)	347mm*350mm*137mm		
Weight	8.5kg		
<b>HMI &amp; COM</b>			
Display	Wireless & APP+LED, LCD (Optional)		
Communication	WiFi (Optional) / GPRS (Optional) / RS485 (Optional)		
<b>Certification</b>			
Safety	IEC62109-1, IEC62109-2		
Grid Code	IEC61727 / 62116, ABNT 16149 / 16150, IEEE 1547, AS 4777		
Warranty	5 Years		

Remarks : • ①②The range of output voltage and frequency may vary depending upon different grid codes.  
• Specifications are subject to change without advance notice.