

SOLAR SERVICES

OUR ENGINEERING OFFICE

FREE TRAINING

an assistance offered on our product to launch your first project (either on-site or via skype).

AN IN DEPTH-STUDY OF YOUR PROJECT

our R&D department can offer you a **custom-made product**. Our expert engagement is to make you an offer within 48 hours.

AN OPTIMIZED STUDY

detailed plans are made to answer all projects requirements, our expertise's will ensure our solution is perfectly adapted to the building site constraints and to all regulatory requirements.

A PRIVILEGED ASSISTANCE

Our team provide an assistance through all needed procedures in particular if your project requires some validation by the Inspection office.

THE SOLAR CLUB SERVICE

As a Dome Solar customer, you can access freely, the SOLAR CLUB SERVICE in order to get some added services and many privileges.

NOTA

📍 | Dome Solar - 3 rue Marie Anderson
44 400 Rezé

☎ | Tél. +33 (0)2 40 67 92 92

✉ | info@dome-solar.com

www.dome-solar.com

OUR PARTNERS

FIBRO SOLAR

METAL AND CEMENT
CORRUGATED ROOFS

PITCHED ROOFS RANGE

EB SOLAR

FIBRO SOLAR

HELIOS B²

ITAL SOLAR

KOGYSUN +

KOGYSUN i+

RB SOLAR

Document printed in France, with vegetable inks, on paper from sustainably managed forests, by Goubault Imprimeur certifié ISO 14001. DANZÉ®



DOME
SOLAR
PHOTOVOLTAIC MOUNTING SOLUTIONS

THE SOLUTION

FIBRO SOLAR solution adapts to most metal and cement corrugated roofs sold on the market.

QUALITY

A robust and durable solution manufactured with premium components made of aluminum.

SIMPLICITY

Ease of installation, with clipping of the rail and clamps.
Ease of earthing system thanks to the continuity of the rail in the slope. Universal clamps for all types of modules thicknesses.



ETN

Assessment
of New
Techniques

MADE IN FRANCE

FIBRO SOLAR

TECHNICAL CHARACTERISTICS

USE CONDITIONS

New or renovated roof, with total or partial covering
Purlin distance: 1,385 m (possibility of making a calculation note)

TYPE OF SUPPORT

Metal and cement corrugated sheets

MODULE POSITION

Landscape mode

MATERIALS

Aluminum and stainless steel

SYSTEM WEIGHT

1 kg/m² excluding the module and the metal or cement corrugated sheets

SUPPORTING STRUCTURE

Metal or wood frameworks

SYSTEM COMPONENTS

4.4 m aluminum rail, rail support, universal and external clamps with an aluminum/stainless steel finish, connector placed at the generator base, locking screw, EPDM joint

OPTIONS

Module Grounding Connector, Rail Grounding Connector, cable guide

www.dome-solar.com