

High Efficiency  
Bifacial PERC Module

# GSM- MP4/108- BMDG415

395W | 400W | 405W  
410W | 415W



**415W**  
Maximum Power Output

**75%**  
Bifaciality

**21.23%**  
Maximum Efficiency

**30Years**  
Linear Power Warranty

## Product Features



### 10BB Half Cell

Multi-busbar half cell design, together with many other technologies to increase module power and efficiency



### High Energy Yield

High density interconnection technology optimizes module efficiency up to 21.23%



### M10 Cell/Module

M10 size cell and module, applicable to multiple scenarios



### High Reliability

Certified mechanical performance up to 5400 Pa positive load and 2400 Pa negative load, with better protection against harsh weather



### Higher Performance

Low temperature coefficient, low operating temperature, more energy yield




### Better Warranty

Low LID/PID in longer service life, less than 15% power degradation in 30 years

## Quality Assurance

**12** Years Product Warranty

**30** Years Linear Power Warranty



## Certificates




**Guosheng Energy Co., Ltd.**

Web: [www.grandsunergy.com](http://www.grandsunergy.com) E-mail: [sales@grandsunergy.com](mailto:sales@grandsunergy.com)

Add: West Side to Zhongjing 7th Road, South Side to Pengcheng Boulevard, Xuzhou Industrial Park, Xuzhou City, Jiangsu Province

## Mechanical Data

Cell(mm)	182×91
Weight(kg)	24.5±0.5kg
Dimension(L×W×H)(mm)	1724×1134×35mm
Cable(mm)	4mm <sup>2</sup> , 300mm(customized length based on needs)
Frame	anodized aluminum
Junction Box	IP68, 1500VDC, 3 Diodes
Packaging Configuration (40'Container; 17.5'Trailer)	31pcs./Pallet; 26pallet/container; 806pcs/container 31pcs/pallet, 36pallet / Trailer, 1116pcs / Trailer



## Electrical Data (STC)

Model	GSM-MP4/108-BMDG395	GSM-MP4/108-BMDG400	GSM-MP4/108-BMDG405	GSM-MP4/108-BMDG410	GSM-MP4/108-BMDG415
Pmax(Wp)	395	400	405	410	415
Voc(V)	36.90	36.98	37.06	37.14	37.31
Isc(A)	13.71	13.78	13.85	13.92	14.01
Vmpp(V)	30.32	30.42	30.52	30.62	30.79
Impp(A)	13.03	13.15	13.27	13.39	13.48
Efficiency	20.20%	20.46%	20.72%	20.97%	21.23%

STC: AM1.5 Irradiance: 1000W/m<sup>2</sup> Temperature=25°C

## Electrical Characteristics (NMOT)

Model	GSM-MP4/108-BMDG395	GSM-MP4/108-BMDG400	GSM-MP4/108-BMDG405	GSM-MP4/108-BMDG410	GSM-MP4/108-BMDG415
Pmax(Wp)	294	297	300	304	308
Voc(V)	33.43	33.52	33.61	33.69	33.86
Isc(A)	11.21	11.26	11.31	11.36	11.40
Vmpp(V)	28.69	28.71	28.73	28.83	28.92
Impp(A)	10.25	10.34	10.45	10.54	10.64

$\alpha_{isc} (\%/K) : 0.05$ ;  $\beta_{Voc} (\%/K) : -0.265$ ;  $\gamma_{Pmp} (\%/K) : -0.34$


NMOT standard: AM1.5 Front irradiance: 800W/m<sup>2</sup> temperature=20°C wind speed=1m/s

## Working Condition

Maximum System Voltage	1500VDC
Operating Temperature	-40°C ~ +85°C
Maximum Fuse Rating	30A
Rear Side Mechanical Load	2400Pa
Front Side Mechanical Load	5400Pa
NOCT	44±2°C
Safty Class	Class II
Grounding Electric Conductivity	< 0.1Ω

## I-V Diagram

(Different Irradiance)



## I-V Diagram

(Different Temperature)

