

LEXRON36

22/42/60/85/105/125/170P

LEXRON

Renewable Energy Systems

LEXRON Solar Modules

Features



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*



PEAK POWER	OPEN CIRCUIT VOLTAGE Voc(V)	SHORT CIRCUIT CURRENT Isc(A)	PEAK VOLTAGE Vmp(V)	PEAK CURRENT IMP (A)	SIZE (mm)	CELL NUMBER (pcs)	NET WEIGHT (kg)
LXR10P	22,10	0,67	18,00	0,56	300*300*25	36	1,3
LXR22P	22,10	1,38	18,00	1,22	430*360*25	36	1,68
LXR42P	22,10	2,58	18,00	2,33	430*670*25	36	3,8
LXR60P	22,10	3,68	18,00	3,33	600*670*25	36	5,2
LXR85P	22,10	4,96	18,00	4,72	800*670*30	36	7,0
LXR105P	22,10	6,10	18,00	5,83	970*670*30	36	8,5
LXR125P	22,10	7,30	18,00	6,94	1150*670*30	36	9,5
LXR165P	22,30	9,30	18,40	8,97	1480*670*30	36	11,9
LXR170P	22,30	9,50	18,60	9,14	1480*670*30	36	11,9

Industry-leading warranty

- 25 years transferable power output warranty: 10 years/90%; 25 years/80%.
- Based on nominal power.
- 10 years material and workmanship warranty.

LEXRON® is registered trade mark of ACS Energy and Technology LTD STI

Add : 1376 Sok. Boran Plaza No:3/AG Halkapınar, Izmir/Turkey

Tel: +90 232 458 0045

E-mail: info@acsenerji.com

www.acsenerji.com