SYM36-6-170M-190M

MONO PERC



About

Twinsel is a manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Twinsel_ s total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

KEY SELIENT FEATURES

























Industry leading lowest temperature co-efficient of power.



Indutry leading 12 years product warranty.



Excellent Low Irradiance Performance.



Excellent PID resistance.



Positive power tolerance of 3%.



Dual stage 100% EL inspection gurantee defect-free product.



Module Imp binning radically reduces string mis-match losses.



Warranted reliability and stringent quality assurances are well beyond cetified requirements.



Certified to withstand severe environmental conditions



- Anti-reflective & anti-soiling surface minimise power losses from dirt and dust
- Severe salt mist, ammonia & blown sand resistance for seaside, farm and desert environments
- Excellent mechanical load 2400Pa & snow load 5400Pa resistance.



电性能参数 (NMOT)			
Maxi.Rated Power(Wp)	190Wp	Solar Cells	36Pcs 156*156mm PERC CELLS.
Voc(V)	24.7	Module Size	1480*680*35MM
Isc (A)	5.16	Weight	11Kgs
Vmp (V)	20.25	3.2 mm, High Transmission, Low Iron, Tempered ARC Glass	
Imp (A)	9.38	4.0mm² (12AWG), 900mm length	
Module Efficiency	19.8%	IP67 MC4 Compatible connector PV-SY02	





Tel: 86-574-59953554 Fax: 86-574-65173959