



DIMENSIONS




I-V CURVE (310)



TEMPERATURE CHARACTERISTICS

Nominal Module Operating Temperature(NOMT)	41±2 °C
Temperature Coefficient of P_{max}	-0.38 %/°C
Temperature Coefficient of V_{oc}	-0.28 %/°C
Temperature Coefficient of I_{sc}	0.020 %/°C



ELECTRICAL CHARACTERISTICS

STC	PNF305M-6X10UW	PNF310M-6X10UW
Maximum Power (P_{max})	305	310
Maximum Power Voltage (V_{mp})	33.0	33.3
Maximum Power Current (I_{mp})	9.25	9.31
Open-circuit Voltage (V_{oc})	40.3	40.5
Short-circuit Current (I_{sc})	9.74	9.81
Module Efficiency (%)	18.1	18.4
Operating Temperature	-40 °C to 85 °C	
Maximum System Voltage	1000 V DC (IEC)	
Maximum Series Fuse Rating	20 A	
Application Class	Class A	
Power Tolerance	0/+5 W	

STC: Irradiance 1000W/m², Cell temperature 25 °C, AM=1.5. Tolerances of P_{max} , V_{oc} and I_{sc} are within ±5%.

NMOT	PNF305M-6X10UW	PNF310M-6X10UW
Maximum Power (P_{max})	229	233
Maximum Power Voltage (V_{mp})	30.5	30.7
Maximum Power Current (I_{mp})	7.51	7.59
Open-circuit Voltage (V_{oc})	37.4	37.6
Short-circuit Current (I_{sc})	7.96	8.04

NMOT: Irradiance 600W/m², Ambient temperature 20°C, AM=1.5, Wind speed 1 m/s.

MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline silicon (158.75mm)
No. of Cells	60 (6×10)
Module Dimensions	1681×1000×2 mm
Weight	5.0kg
Backsheet	White
Frame	Frameless
J-box	IP 68 rated
Output Cables	Photovoltaic technology cable 4.0 mm 2, (+)150 / (-)150 mm
Connector	MC4 compatible

PACKAGING CONFIGURATION

	20' GP	40' HC
Module per pallet	66	66
Pieces per container	396	1584