

12V GEL Series Lead Acid Battery

Key Features:

- Gelled electrolyte made by mixing sulfuric acid with silica fume.
- The electrolyte is gel like, immobile and does not leak, enabling uniform reaction of each part of the plate.
- High rate discharge performance due to tight assembly technology
- Strong heat dissipation and wide operating temperature range
- Avoid acid mist being separated out, environment friendliness
- Efficient venting system release excessive gas automatically



Applications:

- Solar and wind energy storage system
- EPS and UPS battery backup
- Signal system, emergency lighting system, security system
- Telecommunication equipment
- Power plant and transmission system

Model	Voltage(V)	Capacity(Ah)	Weight(KG)	Dimension(MM)				Terminal
				Length	Width	Height	Total Height	
GFM12V2.2	12	2.2	0.82	178	34	60	65	F1
GFM12V3.3	12	3.3	1.45	134	67	60	65	F1
GFM12V4	12	4	1.4	90	70	101	105	F1
GFM12V7	12	7	2.3	151	66	98	103	F2
GFM12V12	12	12	3.5	151	98	95	100	F2
GFM12V17	12	17	6	181	76	167	167	L
GFM12V20	12	20	6.5	181	76	167	167	M5
GFM12V24	12	24	8	175	165	125	125	L
GFM12V33	12	33	10	196	130	174	174	M5
GFM12V40	12	40	12	197	165	175	175	M6
GFM12V55	12	55	16	228	137	207	213	M6
GFM12V65	12	65	19.5	350	166	175	175	M8
GFM12V75	12	75	21.5	260	168	210	215	M6
GFM12V100	12	100	29	330	171	217	220	M8
GFM12V120	12	120	35	412	173	237	237	M8
GFM12V150	12	150	42	484	170	241	241	M8
GFM12V200	12	200	59	522	240	219	225	M8
GFM12V250	12	250	67	520	269	220	228	M8
GFM12V260	12	260	70	520	269	220	228	M8