



ISVE RECYCLING
RECYCLING ENGINEERING PARTNER

MS 40-140 IT SHREDDER

SIEMENS
CONTROL

TOUCH
PANEL


2022

ISVE
MAINTENANCE
PROGRAM

AUTO TUNING
PROGRAM

ISVE SERVER
CONNECT


The MS 40-140 IT single-shaft equipped shredder is particularly suitable to shred high quantities of industrial wastes. The heavy structure makes the machine suitable to realize a heavy use. A hydraulic control unit allows driving the pusher drawer. Thus, the product to be grinded is pushed towards a tools-holder rotor causing its crushing. Thanks to a screen it is possible to select the final dimension of the shredder material.



Main features

Power installed on the rotor:	75 kW (100 HP)
optional:	90 kW (120 HP)
Power of the hydraulic control unit:	5,5 kW (HP 7,5)
Drive:	by belts
Number of rotors:	1
Rotor diameter:	400 mm
Rotor length:	1.300 mm
Pusher stroke:	800 mm
Number of reversible tools:	80
N° of usable tools sides:	4
Upper fixed blades:	5
Lower fixed blades:	5
Average number of rotor revolutions per min:	73
Weight:	6.200 kg
Production:	2,5-3,5 T/h

Safety devices:
emergency stop, drawer reversal system and hydraulic joint.



ISVE Srl

Via San Martino, 39 – 25020 Poncarale (BS) – Italy
Tel. +39 030 2540351 Fax +39 030 2640874
P.IVA: 00942240177 – SDI SUBM70N
www.isve.com – headoffice@isve.com



MS 40-140 IT SHREDDER (2022 VERSION)

Characteristics of the shredder

- Strong welded steel framework;
- Support for barrel roller bearings with sealing system against dust and liquids
- High thickness rotor with diameter of 400 mm and length of 1300 mm. It is equipped with 80 tools-holder plates and 80 high alloyed anti-wear tools usable 4 times;
- No. 10 adjustable counter-blades (5 upper and 5 lower) made in very alloyed anti-wear steel;
- Pusher drawer with hydraulic driving with 800 mm of usable run and no 2 pushing cylinders.
- Hydraulic unit fitted with gear pump with oil cooling radiator;
- Pulleys and belts drive system to avoid damaging mechanical due to rotor vibrations.
- Hydraulic coupling between motor and reduction group.
- No. 1 multi-voltage and multi-frequency motor of 75 KW of primary national company with PREMIUM efficiency class (IE3) and no. 1 motor of 5,5 KW for the hydraulic unit.
- 1300X1300 mm cutting chamber;
- Welded sheet metal hopper for top loading;
- Interchangeable screen establishing the size of the shredded material.
- Discharge system: to be defined

Characteristics of control system

- Electric switchboard complying with EEC standards, equipped with torque limiting device which inverts the direction of the rotor if the work load of the machine exceeds the set value;
- S7-1200 SIEMENS PLC to control all the plant peripheral units;
- Display touch screen 6 inches coloured to regulation of every parameter of the machine;
- New auto-regulation software "AUTO TUNING ISVE";
- Software prepared to control the loading system, the grinder and the suction plant.
- Emergency control functions for stopping the system;
- ISVE MAINTENACE PROGRAM: it signals the ordinary maintenance interventions at their expiry date.
- PREDISPOSITION FOR REMOTE-ASSISTANCE AND "SAFETY SERVER CONNECTION ISVE" (real-time supervision of the parameters from server ISVE);
- **Made to CE standards.**

ACCESSORIES:

ISVE Server Connect: additional system constituted by an Internet connection with automatic monitoring of the proper running of shredding plant by ISVE server. Possibility to adjust machine settings and obtain software updates by remote connection without sending a technician

Interchangeable screen establishing the size of the shredded material (diam. 14-16-20-25-30-35 mm).

Drawer connectable to a suction system

Rotor cooling system.

Wear-resistant coating for rotor.

SPECIFIC ACCESSORIES FOR THE GRINDING OF ELECTRICAL CABLES

Rotor protection plate (prevents rotor overloads when loading hank materials)

Shredder stop software in case of overloaded separation system/refiner mill.

ISVE Srl

Via San Martino, 39 – 25020 Poncarale (BS) – Italy

Tel. +39 030 2540351 Fax +39 030 2640874

P.IVA: 00942240177 – SDI SUBM70N

www.isve.com – headoffice@isve.com

