

# CK600H

STRENGTH IN WASTE



## VERSATILE BALER FOR LARGER VOLUMES

The CK600H is the original CK horizontal baler and has been used by waste recyclers, distribution centres, and companies with large volumes of waste for years. A throughput of up to 2 tonnes per hour can be achieved, depending on material type and loading method.

The 5 wire horizontal tying system and the high shear force provide a solution for a variety of situations.

A wide range of materials can be baled with the CK600H, including cardboard, plastic film, hard plastics, E-Waste, PET, ABS and loose paper.

### BENEFITS

- \_ Second Bale Eject is an economical system to use
- \_ High bale density
- \_ Strong and aggressive shear-blades will cut most materials
- \_ 5 wire horizontal tying system
- \_ 15kW motor and semi-automatic operation
- \_ Cardboard, paper, soft and hard plastics.

### BALER DIMENSIONS

Height	2500mm (to top of standard hopper)
Width	1410mm
Length	5720mm
Weight	Approx 4650kg
Feed Opening (L x W)	1360mm x 720mm

### BALER PERFORMANCE

Compaction Force	50 tonnes
Cycle Time	49 sec / 34 sec
Motor	15kW / 22kW
Power Supply	3 x 415V, 50Hz
Noise Level	80dba

### BALE DIMENSIONS

Height	1080mm
Width	750mm
Length (min - max)	1400mm - 1500mm
Bale Weight Cardboard (approx)	Up to 600kg
Bale Weight Plastic (approx)	Up to 650kg

### CK600H

5 x Steel Wires, Black Annealed	3.5mm dia., 4.6m long
Bale Ejection System	Second Bale Eject
Tying Direction	Horizontal



CK International reserves the right to alter specification without prior notice. Bale weights given are guidelines only, actual bale weights depend on operator and material baled.



CK International Ltd.  
38a Eglish Road  
Dungannon  
Co. Tyrone  
Northern Ireland  
BT70 1LA

T: +44 (0) 28 8775 3966  
F: +44 (0) 28 8772 5528  
info@ckinternational.co.uk  
www.ckinternational.co.uk