

CK600HFE



STRENGTH IN WASTE

VERSATILE BALER FOR LARGER VOLUMES

The CK600HFE is an excellent closed-end horizontal baler that can process up to 3 bales per hour. It is ideal for shredder paper, PET and aluminium cans. It has a 60 tonne compaction force which gives high density bales.

It has a horizontal tying system and full bale eject system which will minimize labour needs.

The CK600HFE is supplied with a hydraulically operated door release system, hinged ejection door, nylon guiding system for press ram, tandem gear pump hydraulics, single cylinder press ram, feed hopper with inspection door, bale full indication and system jammed indication.

BENEFITS

- Shearing knives are replaceable and made from hardened tool grade steel
- Automatic baling cycle and automatic full bale ejection system
- Automatic cut out when bale is full so operator is informed when bale is ready to be tied
- Automatic baling cycle initiated with photo-sensor
- The machine can be supplied with an oil cooling system
- Robust construction for long life
- IP55 rating allows machine to be located outside



BALER DIMENSIONS

Height	2500mm (to top of standard hopper)
Width	1410mm
Length	6280mm
Weight	Approx 5250kg
Feed Opening (L x W)	1000mm x 720mm

BALER PERFORMANCE

Compaction Force	60 tonnes
Cycle Time	40 seconds
Motor	15kW
Power Supply	3 x 415V, 50Hz
Noise Level	80dBa

BALE DIMENSIONS

Height	1100mm
Width	750mm
Length (min - max)	1100mm
Bale Weight Cardboard (approx)	Up to 600kg
Bale Weight Plastic (approx)	Up to 650kg

CK600HFE

5 x Steel Wires, Black Annealed	3.5mm dia., 4.6m long
Bale Ejection System	Full Eject
Tying Direction	Horizontal



CK International reserves the right to alter specification without prior notice. Bale weights given are guidelines only, actual bale weights depend on operator and material baled.

